

The lightweight mast with 101 uses

These telescopic masts are in use world-wide in their thousands. They are in continuous production since 1959 by Clark Masts.

The popularity of QT masts lies in the concept. Aluminium construction for lightness and air pressure



operated for simplicity. The attached handpump provides the air for extension and the air release screw exhausts for retraction. For permanent extension, each section may be locked extended. When wind demands, the mast may be guyed using the guy collar.



Silent, smooth and easy operation

The features that have made it such an attractive and useful piece of equipment are :

1. Aluminium alloy sections
2. Handpump
3. Mounting studs M8
4. Water-drain plug
5. Air-release screw
6. Section-clamping screws
7. Guy collar
8. Quick-clamp for headload

Choose the best QT mast for your purpose

MAST MODEL	Cat. No.	Extended height	Retracted height	Max. recommended headload	Ø Bottom section	Number of sections	Weight of mast	Finish
QT4/HP	8285	4,25m	1,10m	4,5 kg	2 1/2" 63,5 mm	6	6,3 kg	yellow paint
CQT4/HP	25929	4,25m	1,10m	4,5 kg	2 1/2" 63,5 mm	6	6,3 kg	blank anodised
SQT4/HP	9504	4,00m	1,00m	6,0 kg	3" 76,2 mm	7	7,5 kg	yellow paint
CSQT4/HP	25931	4,00m	1,00m	6,0 kg	3" 76,2 mm	7	7,5 kg	blank anodised
QT6/HP	8286	6,10m	1,50m	4,5 kg	2 1/2" 63,5 mm	6	8,2 kg	yellow paint
CQT6/HP	25933	6,10m	1,50m	4,5 kg	2 1/2" 63,5 mm	6	8,2 kg	blank anodised
SQT6/HP	9459	6,10m	1,90m	10,0 kg	2 1/2" 63,5 mm	4	7,3 kg	yellow paint
CSQT6/HP	10865	6,00m	1,90m	20,0 kg	3" 76,2 mm	4	7,3 kg	blank anodised
QT9/HP	8287	9,00m	1,95m	4,5 kg	2 1/2" 63,5 mm	6	10,5 kg	yellow paint
CQT9/HP	25935	9,00m	1,95m	4,5 kg	2 1/2" 63,5 mm	6	10,5 kg	blank anodised
SQT9/HP	9451	8,80m	1,95m	10,0 kg	3" 76,2 mm	6	12,2 kg	yellow paint

CSQT9/HP	25158	9,00m	2,25m	18,0 kg	3" 76,2 mm	5	12,2 kg	blank anodised
QT10/HP	25937	10,00m	2,10m	4,5 kg	2 1/2" 63,5 mm	6	11,0 kg	yellow paint
CQT10/HP	25938	10,00m	2,10m	4,5 kg	2 1/2" 63,5 mm	6	11,0 kg	blank anodised
SQT10/HP	25525	10,15m	2,20m	10,0 kg	3" 76,2 mm	6	13,0 kg	yellow paint
CSQT10/HP	17923	10,15m	2,20m	10,0 kg	3" 76,2 mm	6	13,0 kg	blank anodised
QT12/HP	8388	11,55m	2,00m	2,5 kg	3" 76,2 mm	8	13,2 kg	yellow paint
CQT12/HP	25941	11,55m	2,00m	2,5 kg	3" 76,2 mm	8	13,2 kg	blank anodised
SQT12/HP	25943	12,20m	2,70m	10,0 kg	3" 76,2 mm	6	10,0 kg	yellow paint
CSQT12/HP	25944	12,20m	2,70m	10,0 kg	3" 76,2 mm	6	10,0 kg	blank anodised
QT15/HP	9479	15,00m	2,80m	2,5 kg	3" 76,2 mm	7	18,0 kg	yellow paint
CQT15/HP	25947	15,00m	2,80m	2,5 kg	3" 76,2 mm	7	18,0 kg	blank anodised
SQT15/HP	25519	15,00m	2,80m	10,0 kg	3 1/2" 88,9 mm	7	21,0 kg	yellow paint
CSQT15/HP	25949	15,00m	2,80m	10,0 kg	3 1/2" 88,9 mm	7	21,0 kg	blank anodised

QT mast mounting accessories

GROUND MOUNTING



Tripod Stand MK IV Cat. No. 9427

This very stable stand folds horizontally for storage. It may be further dismantled without tools for transport.



Tripod Stand MK V
Cat. No. 25164

This stand is suitable for masts up to 6 metres high. It is similar to the MK IV stand above but has shorter legs.

MOUNTING MAST ON VEHICLE OR SHELTER

Saddle Clamps

These clamps, usually used in pairs, are for mounting the mast on any suitable vertical surface, making the mast instantly removable.



Cat. No. 13780
(2 1/2" Base Masts)



Cat. No. 2433
(3" Base Masts)



Cat. No. 1984
(2 1/2" Base Masts)



Cat. No. 9920
(3" Base Masts)

There is a full range of accessories for mounting QT masts in the field or attaching them to vehicles or shelters. Full details are given on technical data sheet ref. PP 2024

CLARK MASTS™

All details given in this publication are approximate and may be subject to change without notice.

Distributor :

CLARK MASTS TEKSAM NV, Woudstraat 21, B-3600 Genk, Belgium

Tel : +32 (0)89 38 44 72 - Fax : +32 (0)89 38 61 41 - E-mail : info@teksam.be - Website : www.clarkmasts.be

CLARK MASTS is a division of Clark Masts Teksam NV

PIONEER IN FAST ERECTING MAST SYSTEMS