



# TF 300E T Series

## *Turnable middle-range mast lighting systems*

Teklite TF 300E T lighting system with turnable air-operated telescopic mast, keyed mast sections, internal spiral cable and lamps either 12/24 volt powered by the vehicle battery or 110/230 volt generator powered.



The Teklite TF 300E T series of mast lighting systems are especially designed for directional lighting applications. Ideal for fitting to medium size fire vehicles. Teklite TF 300E T series combines high quality lighting performance with reasonable costs.

**MOBILE, PORTABLE & EMERGENCY LIGHTING**

# Mast specifications

## Technical details



1 Mast top assembly with 1 x PG9, 1 x PG11, 1 x PG13,5 cable gland and 8 mm top flange fitted to keyed mast sections



4 Standard pre-mounted and connected warning switch



2 Standard natural clear anodised seamless drawn aluminium mast sections with 80 mm base tube and swivel rotation handle



5 Rubber protection rings, shock-absorbing



3 360° turnable cardan mast base with air connection, overpressure/drain valve and rotation brake



6 Power supply cable (5 metres) with numbered wires for lamp/beacon connection

## TF 300E T Series mast models (Class II approved)

Model	Cat. No.	Retracted height	Extended height	Internal cable	Weight of mast
<b>3 SECTION MASTS</b>					
TF 326E T/3	25486	1225 mm	2630 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	11,0 kg
TF 335E T/3	25487	1575 mm	3530 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	12,0 kg
TF 340E T/3	25488	1730 mm	3930 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	12,5 kg
TF 350E T/3	25489	2105 mm	4900 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	15,0 kg
<b>4 SECTION MASTS</b>					
TF 335E T/4	25641	1370 mm	3470 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	11,8 kg
TF 340E T/4	25642	1495 mm	3970 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	12,3 kg
TF 347E T/4	25645	1670 mm	4750 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	14,4 kg
TF 350E T/4	25643	1785 mm	4950 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	15,1 kg
TF 355E T/4	25644	1910 mm	5450 mm	9 x 1.5 + 4 x 0.75 mm <sup>2</sup>	16,0 kg

### Mast mounting

These mast fittings are available for mounting the mast inside or outside the body of the vehicle.

#### External mounting



**Upper Mounting Bracket**

Cat. No. 16681/SG



**Lower Mounting Bracket**

Cat. No. 16686/SG

#### Internal mounting



**Roof Bearing**

Cat. No. 25803/SG

# Lamp choice

\* Lamp unit available with beacon & bracket (option). Put a "B" after the lamp unit cat. no. for ordering purposes.

\* Lamp unit available with lamp protection guard (option). Put a "P" after the lamp unit cat. no. for ordering purposes.

## Double lamp unit, 2 lamps mounted above the bar \*

Cat. No.	Model	Volt	Amps	Lumens
26085	2 x 70 Watt HP Sodium*	12	12,5	13.000
26090	2 x 70 Watt HP Sodium*	24	7,0	13.000
26095	2 x 70 Watt Metal Halide*	12	13,0	10.000
26100	2 x 70 Watt Metal Halide*	24	7,4	10.000
26105	1 x 70 Watt HP Sodium + 1 x 70 Watt Metal Halide*	12	12,8	11.500
26110	1 x 70 Watt HP Sodium + 1 x 70 Watt Metal Halide*	24	7,2	11.500
26115	2 x 35 Watt Xenarc	12	5,9	7.000
26120	2 x 35 Watt Xenarc	24	3,0	7.000
26125	2 x 100 Watt Xenon*	12	16,7	7.200
26135	2 x 150 Watt Xenon*	24	12,5	12.000
26130	2 x 200 Watt Xenon*	12	33,4	14.400
26140	2 x 300 Watt Xenon*	24	25,0	24.000
26145	2 x 500 Watt Halogen*	230	4,4	19.000
26148	2 x 750 Watt Halogen*	230	6,5	33.000
26150	2 x 1000 Watt Halogen*	230	8,7	44.000
35791	2 x 50 Watt SMD-LED*	12	10,6	10.000
35796	2 x 50 Watt SMD-LED*	24	4,8	10.000

## Double lamp unit, 2 lamps mounted below the bar \*

Cat. No.	Model	Volt	Amps	Lumens
26155	2 x 70 Watt HP Sodium*	12	12,5	13.000
26160	2 x 70 Watt HP Sodium*	24	7,0	13.000
26165	2 x 70 Watt Metal Halide*	12	13,0	10.000
26170	2 x 70 Watt Metal Halide*	24	7,4	10.000
26175	1 x 70 Watt HP Sodium + 1 x 70 Watt Metal Halide*	12	12,8	11.500
26180	1 x 70 Watt HP Sodium + 1 x 70 Watt Metal Halide*	24	7,2	11.500
26185	2 x 35 Watt Xenarc	12	5,9	7.000
26190	2 x 35 Watt Xenarc	24	3,0	7.000
26195	2 x 100 Watt Xenon*	12	16,7	7.200
26205	2 x 150 Watt Xenon*	24	12,5	12.000
26200	2 x 200 Watt Xenon*	12	33,4	14.400
26210	2 x 300 Watt Xenon*	24	25,0	24.000
26215	2 x 500 Watt Halogen*	230	4,4	19.000
26218	2 x 750 Watt Halogen*	230	6,5	33.000
26220	2 x 1000 Watt Halogen*	230	8,7	44.000
35801	2 x 50 Watt SMD-LED*	12	10,6	10.000
35806	2 x 50 Watt SMD-LED*	24	4,8	10.000

## Triple lamp unit, 1 lamp mounted above and 2 lamps below the bar

Cat. No.	Model	Volt	Amps	Lumens
26225	3 x 70 Watt HP Sodium*	12	18,8	19.500
26230	3 x 70 Watt HP Sodium*	24	10,5	19.500
26235	3 x 70 Watt Metal Halide*	12	19,5	15.000
26240	3 x 70 Watt Metal Halide*	24	11,1	15.000
26245	3 x 35 Watt Xenarc	12	8,8	10.500
26250	3 x 35 Watt Xenarc	24	4,4	10.500
26260	3 x 100 Watt Xenon*	12	25,0	10.800
26275	3 x 150 Watt Xenon*	24	18,8	18.000
26265	3 x 200 Watt Xenon*	12	50,0	21.600
26280	3 x 300 Watt Xenon*	24	37,5	36.000
26285	3 x 500 Watt Halogen*	230	6,5	28.500
35811	3 x 50 Watt SMD-LED*	12	15,9	15.000
35816	3 x 50 Watt SMD-LED*	24	7,2	15.000

A lot of lamp unit combinations are possible, some of them are shown below.

Model 2 x 70 Watt HP Sodium\*



Model 2 x 200 Watt Xenon\*\*



Model 2 x 150 Watt Xenon\*\*



Model 2 x 1000 Watt Halogen\*\*



Model 3 x 500 Watt Halogen\*



Model 3 x 35 Watt Xenarc



\* Lamp unit available with beacon & bracket (option). Put a "B" after the lamp unit cat. no. for ordering purposes.

\* Lamp unit available with lamp protection guard (option). Put a "P" after the lamp unit cat. no. for ordering purposes.

### **Triple lamp unit, 3 lamps mounted above the bar**

Cat. No.	Model	Volt	Amps	Lumens
26290	3 x 70 Watt HP Sodium*	12	18,8	19.500
26295	3 x 70 Watt HP Sodium*	24	10,5	19.500
26300	3 x 70 Watt Metal Halide*	12	19,5	15.000
26305	3 x 70 Watt Metal Halide*	24	11,1	15.000
26310	3 x 35 Watt Xenarc	12	8,8	10.500
26315	3 x 35 Watt Xenarc	24	4,4	10.500
26325	3 x 100 Watt Xenon*	12	25,0	10.800
26340	3 x 150 Watt Xenon*	24	18,8	18.000
26330	3 x 200 Watt Xenon*	12	50,0	21.600
26345	3 x 300 Watt Xenon*	24	37,5	36.000
26350	3 x 500 Watt Halogen*	230	6,5	28.500
35821	3 x 50 Watt SMD-LED*	12	15,9	15.000
35826	3 x 50 Watt SMD-LED*	24	7,2	15.000

### **Quadruple lamp unit, 2 lamps mounted above and 2 below the bar \***

Cat. No.	Model	Volt	Amps	Lumens
26355	4 x 70 Watt HP Sodium*	12	25,0	26.000
26360	4 x 70 Watt HP Sodium*	24	14,0	26.000
26365	4 x 70 Watt Metal Halide*	12	26,0	20.000
26370	4 x 70 Watt Metal Halide*	24	14,8	20.000
26375	2 x 70 Watt HP Sodium + 2 x 70 Watt Metal Halide*	12	25,6	23.000
26380	2 x 70 Watt HP Sodium + 2 x 70 Watt Metal Halide*	24	14,4	23.000
26385	4 x 35 Watt Xenarc + DC-DC Power Converter	12	11,7	14.000
26390	4 x 35 Watt Xenarc	24	5,9	14.000
26395	4 x 100 Watt Xenon*	12	33,4	14.400
26400	4 x 150 Watt Xenon*	24	25,0	24.000
26405	4 x 300 Watt Xenon*	24	50,0	48.000
26410	4 x 500 Watt Halogen*	230	8,7	38.000
35831	4 x 50 Watt SMD-LED*	12	21,2	20.000
35836	4 x 50 Watt SMD-LED*	24	9,6	20.000

### **Quintuple lamp unit, 3 lamps mounted above and 2 below the bar**

Cat. No.	Model	Volt	Amps	Lumens
26415	5 x 35 Watt Xenarc	24	7,3	17.500
26420	5 x 100 Watt Xenon*	12	41,7	18.000
26425	5 x 150 Watt Xenon*	24	31,3	30.000
26430	5 x 500 Watt Halogen*	230	10,8	47.500
35841	5 x 50 Watt SMD-LED*	12	26,5	25.000
35846	5 x 50 Watt SMD-LED*	24	12,0	25.000

A lot of lamp unit combinations are possible, some of them are shown below.

**Model 3 x 500 Watt Halogen\***



**Model 3 x 35 Watt Xenarc**



**Model 4 x 70 Watt HP Sodium\***



**Model 4 x 500 Watt Halogen\*\***



**Model 5 x 150 Watt Xenon\***



**Model 5 x 35 Watt Xenarc**



# Air supply for mast extension

The air pressure for mast extension may be provided by a battery powered compressor or from the vehicle air pressure system.

## Using the vehicle battery power



### Compressor Model 40/50

#### IMPORTANT NOTE :

All our compressors are supplied with a NO (normal open) valve. They need permanent current during operation of the mast lighting system. However, when there are applications where there is no permanent current available (e.g. mast fitted to a standalone container), apply for a compressor with a NC valve.



### Remote Control for Model 40/50 Compressor

The complete remote control set is delivered with 5 metre cable and connection plug.

#### Models with NO Valve

Model 40/50, 12 volt	Cat. No. 33640
Model 40/50, 24 volt	Cat. No. 33642

#### Models with NO Valve and Deadman Function

Model 40/50, 12 volt	Cat. No. 33641
Model 40/50, 24 volt	Cat. No. 33643

#### Models

Model 12 volt	Cat. No. 25798
Model 24 volt	Cat. No. 25799

#### Models with Deadman Function

Model 12 volt	Cat. No. 25220
Model 24 volt	Cat. No. 25221

## Using the vehicle air pressure system



### Air Pressure Control Unit

Combined unit consisting of manometer, pressure regulator and control handle.

#### Models

AP Control Unit	Cat. No. 25218
AP Control Unit with Deadman Function	Cat. No. 25219



All details given in this publication are approximate and may be subject to change without notice.

Distributor :

**CLARK MASTS TEKSAM NV**, Woudstraat 21, B-3600 Genk, Belgium

Tel : +32 (0)89 38 44 72 - Fax : +32 (0)89 38 61 41 - E-mail : info@teksam.be - Website : www.teklite.com

TEKLITE is a division of Clark Masts Teksam NV

ISO 9001:2000 CE

PP 1293/E NV - MM 29/06/10